


CINCINNATI MACHINES

AccuSIZE

Precision Internal Grinders



ACCUSIZE CNC

Accusize Precision Internal Grinder with CNC Control



ACCUSIZE



Accusize Precision Manual Internal Grinder with PLC Control

ACCUSIZE

State-of-the-Art Precision Internal Grinding

ACCUSIZE State-of-the-Art Precision Internal Grinders combine World Class control and drive technology with time proven Cad Generated Machine Geometry and Rock Solid Seasoned Meehanite Castings to provide cutting Edge Internal Grinding capabilities, yet they are very affordable.



CAD Generated Machine Geometry

CAD Generated Machine Geometry insures that every phase of these machines have been totally optimized to provide the very best internal grinding capabilities

Rock Solid Seasoned Meehanite Casting

CAD Generated Rock Solid Meehanite Castings insure rigid and non twisting grinds without deflection, to provide maximum accuracy and consistency.

ACCUSIZE

ACCUSIZE CNC
shown with optional
full enclosure



Brand new face grinding attachment (Optional)



ACCUSIZE II

TWIN SPINDLE INTERNAL GRINDER



Twin Spindles - Double Productivity

Twin-Spindles = ID/OD and up to 16
Grind Operations in one setup.



ACCUSIZE II

TWIN SPINDLE INTERNAL GRINDER

User-friendly operation interface




AccuSize II comes equipped with the FANUC CNC control system as standard. In addition, the MPG (Manual Pulse Generator) Handwheel provides the operator with easy means to move the machine slides around for quick part setup. In addition, the operator will have very easy and simple access to controls for both Grinding Spindles.

Unique Twin-Spindle Design

AccuSize II's main feature is the unique 2-Spindle design that allows up to 16 different ID/, OD, and or Face grinding operations to be included in one setup. This capability will add whole new dimensions to your grinding capabilities.



AccuSize II for extra-long parts



ACCUSIZE XL

TWIN SPINDLE LONG PART INTERNAL GRINDER



Specifically Designed for Long Parts



ACCUSIZE XL


World-Class Fanuc CNC

ACCUSIZE XL comes equipped with the FANUC CNC control system as standard. In addition, the MPG (Manual Pulse Generator) Handwheel provides the operator with easy means to move the machine slides around for quick part setup. In addition, the operator will have very easy and simple access to controls for both Grinding Spindles.



Unique Twin-Spindle Design

ACCUSIZE XL combines the unique 2-Spindle design with the capability to grind long parts with lengths up to 23.4". Now, you can grind those long parts and allow up to 16 different ID/, OD, and or Face grinding operations to be included in one setup. This capability will add whole new dimensions to your long part grinding capabilities.



Model	ACCUSIZE	ACCUSIZE w/FACING	ACCUSIZE II	ACCUSIZE XL
Grinding diameter range	Ø0.16" ~ Ø9.4"	Ø0.16" ~ Ø7.8"	Ø0.16" ~ Ø12.6"	Ø0.16" ~ Ø5.8"
Max. grinding depth	5.9"	5.9"	7.8"	7.8" (23.4" part Length)
Swing over table	15"	15"	13.7"	11.7"
Swing over splash guard	Ø12.6"	Ø7.8"	Ø12.6"	N/A
Control	FANUC	FANUC	FANUC	FANUC
Spindle speed	0 ~ 1000 rpm	0 ~ 1000 rpm	0 ~ 1000rpm	0 ~ 1000 rpm
X Axis feed rate	394in/min	394in/min	394 in/min	394in/min
X Axis travel	11.8"	11.8"	15.3"	12.9"
Min. unit of X Axis movement	0.0001"	0.0001"	0.0001"	0.0001"
Workhead swiveling angle	-5° ~ +15°	-5° ~ +15°	-5° ~ +30°	N/A
Max. feed rate of Y / Z Axis	Z: 394 in/min	Z: 394 in/min	394/394in/min	Z: 394 in/min
Y / Z Axis travel	Z:15.7"+3.9"	Z:15.7"+3.9"	13.7"+7.8"/13.7"+7.8"	Z: 14.8"+6.2"
Min. unit of Y / Z Axis movement	0.0001"/0.0001"	0.0001"/0.0001"	0.0001"/0.0001"	0.0001"/0.0001"
Distance from wheel center to floor	41.7"	41.7"	41.7"	41.7"
Hyd. Oil tank capacity	7.5 gal.	7.5 gal.	7.5 gal.	7.5 gal.
Coolant tank capacity	37.5 gal.	37.5 gal.	50 gal.	37.5 gal.
Hyd. Pump motor	0.75 Kw (1HP)	0.75 Kw (1HP)	0.75 Kw (1HP)	0.75 Kw (1HP)
Coolant pump	0.18 Kw (1/4HP)	0.18 Kw (1/4HP)	0.18 Kw (1/4HP)	0.18 Kw (1/4HP)
X / Y / Z Axis servo motor	X: 1.2Kw / Z:1.2 Kw	X: 1.2Kw / Z:1.2 Kw	1.6 / 1.6 / 1.6 Kw	X: 1.2Kw / Z:1.2 Kw
Grinding wheel motor (B1/B2) (KW)	B1:2.2,2P(3HP)	2.2, 2P (3HP) / 4.5 (6HP)	2.2, 2P (3HP) / 2.2, 2P (3HP)	2.2, 2P (3HP) / 4.5 (6HP)
Workhead motor	2.2 Kw, 4P (3HP)	2.2 Kw, 4P (3HP)	2.2 Kw, 4P (3HP)	2.2 Kw, 4P (3HP)
Automatic lubricator	0.5gal.	0.5gal.	1 gal.	0.5gal.
Machine dimensions (L x W x H)	87"X91"X67"	87"X91"X67"	98"x83"x77"	87"X91"X67"
Machine weight	6600 lbs.	6600 lbs.	10,450 lbs.	6600 lbs.

*Specifications and design are subject to change without prior notice. *

CINCINNATI MACHINES

900 Dalton Ave. Cincinnati, Ohio 45203 USA
 513 681-1953 888-999-5897
 sales@cinmac.com parts@cinmac.com
 www.cinmac.com